A L X

Application Remote Control Instruction Manual

(Android Version)

For Users

Product Type: NE-Z41, NE-Z41SH

Document Number: 81-SS00124 (ver.5)

Application Ver. 0.4.8 or later

Date of issue : 2024-04-01

Language: English



- Carefully read the instruction manual prior to use.
- ■Keep this instruction manual for future reference.

Nabtesco

Nablesco Corporation



Introduction

Thank you for purchasing Nabtesco's ALLUXTM.

Matters concerning typical usage such as fitting and walking, maintenance, trouble shooting, and cautionary notes are described in the User's Guide that comes with an ALLUXTM (hereinafter referred to as the User's Guide).

This Application Remote Control Instruction Manual (hereinafter referred to as this manual) describes how to install and use the Application Remote Control (hereinafter referred to as this App) in the Android system environment.

For safe and comfortable use, thoroughly read the User's Guide mentioned above and this manual, sufficiently understand the contents, and strictly observe the safety precautions stated in those documents.

- Nabtesco owns the copyright for this document.
- Android is a registered trademark of Google Inc. in the United States and other countries.
- Google is a trademark of Google Inc.
- Google Play and Google Play logo are trademarks of Google Inc.
- The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG. Inc. and any use of such marks by Nabtesco Corporation is under license.
- QR code is a registered trademark of Denso Wave Incorporated.
- All other company names and product names are trademarks or registered trademarks of their respective companies.

Table of contents

ın	troduci	tion	1
Ta	able of	contents	2
1	Sup	ported model and operating environment······	3
2	Insta	all procedures and initial settings······	4
	2.1	Installation procedures	4
	2.2	Bluetooth pairing	5
3	Safe	posture	6
4	Com	nmunication mode and how to connect Bluetooth·····	7
5	ALL	UX TM operational modes······	8
6	Initia	al settings ·····	· 10
7	Mod	le change screen ·····	· 12
8	Con	nection to ALLUX TM screen······	· 13
9	Acq	uisition of data screen······	· 14
1() Gen	eral screen·····	- 15
11		er settings screen·····	
12	2 Abo	ut ALLUX [™] screen ······	· 17
13	3 Mod	le name screen·····	- 18
14	1 Erro	r message popup·····	- 19
	14.1	Location information error A	- 19
	14.2	Location information error B	- 19
	14.3	Bluetooth setting error ·····	
	14.4	Connection to ALLUX TM error ······	-20
	14.5	Password error (3 times) · · · · · · · · · · · · · · · · · · ·	-20
	14.6	Wireless connection error	-20
	14.7	Wireless communication error ·····	-20
	14.8	Safe posture error	-20
	14.9	Hydraulic control error ·····	-21
		Device connection error in the vicinity	
	14.11	Reconnect button error ·····	-21
1	5 Troi	ıbleshooting	. 22

Supported model and operating environment

●ALLUX[™] (type: NE-Z41)

*ALLUXTM (type: NE-Z4) is not supported.

The model can be identified by the design of the front link pad. It can also be identified by the indication on the charging port.



NE-Z41 (Supported type)



NE-Z4 (Non-supported type)



NE-Z41 (Supported type)



NE-Z4 (Non-supported type)

Compatible OS: Android 7 or later

This App is compatible with the OS of Android 7 or later, but it doesn't guarantee that it will work on all Android devices.

Free storage space: 500 MB or more is recommended.

Bluetooth[®]

Precautions on Bluetooth

- Radio waves emitted by a Bluetooth device may affect the operation of electronic devices and other devices. Turn off Bluetooth devices when near priority seats in trains, in areas where flammable gas is generated such as in airplanes near automatic doors and fire alarm devices, as it may cause an accident.
- We do not take any responsibility for the leakage of information when using Bluetooth technology.
- This product does not guarantee wireless connection with all Bluetooth devices. The Bluetooth device to be connected must comply with the Bluetooth standard specified by Bluetooth SIG and must have obtained at least a certification. In addition, even if the device to be connected complies with the Bluetooth standard, phenomena such as inability to connect or different display/operation may occur, depending on the characteristics and specifications of the device.
- Do not disassemble or modify this product as the wireless functionality of this product has been certified to meet technical standards.


Install procedures and initial settings 2

2.1 Installation procedures

1. Sign in with your Google ID.

Type the App name "ALLUX2" into the Search field.

Tap the utton on the keyboard.





The following QR code can be used to install.



2. After the search results are displayed, tap the target App as shown below.



- 3. Tap the "Install" button.
- 4. After the installation is completed, the icon of the App is created on the home screen of the smartphone.
- 5. Tap the icon to start the App.




Install procedures and initial settings

2.2 Bluetooth pairing


Bluetooth pairing is required before using this App.

Follow the procedure below for pairing.

- *The procedure and screen will differ depending on your smartphone and the version of the Application. Please check the manual for your smartphone.
- Remove the power OFF cap from ALLUXTM to enable ALLUXTM to communicate.
 - *The power is turned on when the power off cap is removed and turned off when it is inserted. (Refer to page 7)
- Tap Bluetooth from the Settings button or Device Connections, etc. Select ALLUX: XXXXXXX from the available devices and tap Allow or Pair if permission is required.



When paired correctly, the display will look like this



Insert the power-off cap of ALLUXTM to disconnect pairing with ALLUXTM.

Before changing the operational mode of ALLUX™ using the Application Remote Control, the user needs to take a posture which is safe even if hydraulic resistance changes. This posture is referred to as 'safe posture'. Be sure to understand the following safe postures before using ALLUXTM.

[Safe posture]



The ALLUXTM is fully straighten, stable and will be safe to place your body weight on it.



: Weight is off of the ALLUXTM, but it may be bent.




■ When taking the safe posture without applying the body weight to ALLUXTM, hold a handrail or sit down.

You may lose your balance and fall over.

[Request for safe posture]

If ALLUX 2TM is not in the safe posture when changing the operational mode of ALLUXTM, a popup is displayed. Make sure you have the safe posture, and tap "OK" button.



Communication mode and how to connect Bluetooth

In order to conserve power, ALLUXTM is not always in communication mode.

In order to enable the communication mode, you need to perform the following operations.

Once ALLUXTM communication is established using this App, this state lasts until communication is disconnected.

[Communication mode enabled]

- 1. For 5 minutes after ALLUXTM is slightly flexed and extended.
- 2. For 5 minutes after you apply your body weight to ALLUX™.
- 3. For 5 minutes after the charger or the power OFF cap is disconnected from ALLUX™.








It is possible to turn OFF wireless connection when the user gets on a plane, etc. To restore wireless connection from that state, the actions such as the one shown below are required.

- 1. Disconnect the charger or the power OFF cap form ALLUX™.
- 2. "Apply a load on the heel 4 times intermittently" or "Apply a load on the toe 4 times intermittently" *You can switch to either one you like by a method described in page 14.



- *Just starting this App does not connect to ALLUXTM. Tap the Bluetooth icon on the "Mode Change" screen (Refer to page 12) to connect to ALLUXTM.
- *Just tapping the home button etc. on the smartphone does not disconnect communication with ALLUXTM and this App keeps working behind the screen. If you tap the icon of this App again, it starts in the connected state.



■ Do not turn off the smartphone or force-quit this App while changing a mode with this App. Doing so may cause adjustment values to turn into an unintended state and result in a fall.

NOTICE

■ Even if this App is hidden on the smartphone, the connection with ALLUXTM is maintained and the battery of the smartphone keeps being consumed. If you are concerned about battery consumption, disconnect the smartphone from ALLUXTM or close this App.

ALLUX™ operational modes


ALLUXTM has the following five operational modes.

[Normal mode]

The normal mode is adjusted for normal walking. Judging various walking situations and normal motions with the sensor, ALLUXTM automatically adjusts the flexion and extension.


[Flexion angle limit mode]

In flexion angle limit mode, flexion resistance is locked at a designated angle while extension resistance remains free.



[Variable selective flexion lock mode]

ALLUXTM remembers the angle at which variable selective flexion lock mode is turned on. Flexion resistance is locked when it reaches that angle while extension resistance remains free.




NOTICE

■ When the flexion angle limit mode or variable selective flexion lock mode is used, do not apply excessive force to ALLUXTM when locking it. If an excessive impact force is applied to ALLUXTM, it may be damaged.

5 ALLUX[™] operational modes


[Full extension lock mode]

ALLUXTM is locked in a fully extended state.



[Free swing mode]

In free swing mode, ALLUXTM is kept free (resistance-free state).



Each of these operational modes can be assigned to the buttons in the Application Remote Control by the prosthetist using the Adjustment App, and you can change to a mode you want by tapping the corresponding button on the "Mode Change" screen of the Application Remote Control. (page 12) The normal mode is always assigned to Button 1 on the Application Remote Control.

You can freely assign the five operational modes above to buttons 2 to 5 on the Application Remote Control.

Default remote controller configuration:

- Button 2: Flexion Angle Limited mode
- Button 3: Variable Selective Flexion Lock mode
- Button 4: Full Extension Lock mode
- Button 5: Free Swing mode

6


Initial settings 6

- *The pop-up screen will vary depending on the smartphone you are using.
- Tap the icon of this App to start.




A popup is displayed asking for permission for this App to access the smartphone's location. Tap "Allow".

Android 12 or later versions do not use location information. A popup will appear asking for permission regarding nearby devices, please allow it.




The "Legal & Regulatory" dialog is displayed. Read it and tap the "OK" button.



6) Initial settings

- The company logo is displayed. From the second time, the above screens are skipped and this screen is displayed when you tap the icon of this App.
 - After the company logo is displayed on screen for a second, this screen is automatically changed to next screen.




A warning popup is displayed. Read it and tap the "OK" button.



Mode change screen

"Mode Change" screen is displayed after the warning popup.



Reconnect icon:

Tap this icon to connect to the previously connected ALLUXTM. The following popups are displayed before and after the connection





Bluetooth icon:

Tap this icon to display the "Connection to ALLUX™" screen (page 13). The icon changes depending on the connection state. When it is in a disconnected state, tap the icon to enable connection



Disconnected

Connected

General icon:

Tap this icon to display the "General" screen (page 15).

Standby mark:



While this App is communicating with ALLUXTM or performing other processing, a standby mark is displayed. While this mark is displayed, all on-screen operations are disabled.

Remote control button:

When you tap one of these buttons, the state of ALLUXTM changes to the operational mode which was assigned by the prosthetist beforehand. When you tap the button, a popup is displayed. Tap the "OK" button.

Screen change tab:

You can switch between the "Mode Change" screen and "Acquisition of Data" screen. Tap on these characters or slide each screen to left or right to switch the screen.

Total steps:

It shows the number of steps you have made up to this point.

Daily Steps

It shows the number of steps you made on the day.

Scheduled periodic inspection:

If you entry the start date of use in the "Other settings" of the General icon, the scheduled date of the periodic inspection will be displayed.

Latest adjustment date:

It shows the date when ALLUXTM was in last adjusted.

Vibration alarm demo button:

ALLUXTM vibrates in demo.

Battery level:

It shows the battery level of ALLUXTM.









10% or less

10~40%

40~70% 70% or more

8

Connection to ALLUX[™] screen



- 1. On the "Connection to ALLUXTM" screen, scanning for wireless devices automatically starts.
- 2. The devices related to ALLUXTM are listed up. The indicated characters vary based on the serial number of $ALLUX^{TM}$.

The third line indicates the connection state.

- Disconnected
- Connecting
- Connected
- 3. "ALLUX:Serial No" is displayed. If more than one device is listed up, according to the Serial No. of your ALLUX[™], select the appropriate wireless device.
- 4. If the wireless device for ALLUXTM is not listed up, the wireless connection of ALLUXTM may be in sleep mode. Activate the wireless connection referring to page 7 After that, tap the "Cancel" button and then tap the "Scan" button displayed in that position to search for wireless devices again.
- 5. Tap the wireless device on the list. If the wireless connection is successfully done, the "Mode Change" screen (page 12) is displayed automatically.


When connecting to ALLUXTM for the first time the screen of "Connection to ALLUXTM" is displayed. Enter the password indicated on the charging port of ALLUXTM. If you fail in entering the password 3 times, you need to restart this App.





Acquisition of data screen

You can check the state of ALLUXTM on this screen.




9

Current Temperature: You can check the temperature of ALLUXTM. Repeated yielding motion may cause high temperature. When ALLUX™ gets hot, it enters high temperature mode and you cannot walk.

- Total Steps: It shows the number of steps you have made up to this point.
- Daily Steps: It shows the number of steps you made on the day.
- Pedometer: When you tap the "Reset pedometer" button, the number of steps becomes 0 once and then it starts to show the number of steps you make from that point.
- Battery: It shows the battery level. (The displayed marks are the same as those shown in page 12.)
- Vibration for safety lock: This button is used to set whether or not to vibrate the ALLUXTM when the safety lock (page 10 of the User's Guide) is enabled.
- Reconnection method: This button is used to change the method to return wireless connection to ON without using the charger or the power OFF cap when wireless connection was turned OFF to get on a plane, etc. Refer to page 7.
- Current ALLUXTM Mode: Shows the current walking mode. Refer to page 8.
- Data acquisition button: When you tap this button, information such as the number of steps is updated.

10 **General screen**

When you tap the General icon : on the "Mode Change" screen or the "Acquisition of Data" screen, the screen displays the "General" screen.



- About ALLUXTM:
 - "About ALLUXTM" screen (page 17) is displayed.
- Change the name of mode: "Mode Name" screen (page 18) is displayed.
- Other settings:

"Other settings" screen (page 16) is displayed. In this screen, you can set whether to automatically connect to the previously connected ALLUXTM when the App starts, set whether to confirm when changing modes, and enter the start date of use.

Airplane mode:

A popup is displayed. Tap the "OK" button to turn OFF ALLUXTM wireless connection.

Reboot:

When you tap this button, a popup is displayed. Tap the "OK" button to reboot ALLUXTM.

* As the communication is disconnected, you need to enable connection again.

(The same action as removing and inserting the power OFF cap.)

Instruction Manual:

Download the instruction manual from jumped link.


Legal & Regulatory:


The "Legal & Regulatory" dialog (page 10) is displayed.

About APP:

Displays application name, usage, UDI-DI, etc.

Other settings screen






Automatic connection at startup:

You can set whether to automatically connect to the previously connected ALLUXTM when the App starts.

- Skip confirmation when changing modes: You can set whether to display a confirmation popup when you click a button for changing mode.
- Start date of use:

You can enter the start date of use. This entry is required when displaying the scheduled periodic inspection date.

About ALLUX[™] screen



App Version:

The version of this App is displayed.

- ALLUXTM firmware version: The firmware version of ALLUX $^{\text{TM}}$ is displayed.
- Serial No:


The serial number of the ALLUX $^{\text{TM}}$ is displayed.

Mode name screen

ALLUXTM allows to freely assign the operational modes described in page 8 to the buttons on the Application Remote Control. ALLUX™ also allows to change the button names indicated on the "Mode Change" screen. Be sure to check the assignment with the prosthetist and change the button names according to the assignment.

It is convenient to name the buttons according to the adjustment values, for example, 'Normal mode (for a shoe with a high heel)' or 'Flection Angle Limited mode (50 deg.)'.

If the prosthetist changes the mode assignment, the mode names return to the defaults.



- 1. Tap the operational mode to change the name.
- 2. A keyboard is displayed on the screen.
- 3. Enter a new name.
- 4. Tap "✓" to complete the entry.
- 5. Once return to "Mode Name" screen, the name is reflected to this App.

14 **Error message popup**

If an error occurs during an operation, a popup is displayed.

Please follow the instructions in the popup.

14.1 Location information error A

ALLUX™ Remote Control

Go to Settings-> Apps-> "ALLUX™ Remote Control"-> Permissions and turn on location.

App closes when the "OK" button is pressed.

OK

Location information is required to use "ALLUXTM Application Remote Control". Therefore, you need to have set to allow this App to access the location information of the smartphone in the operation in page 10. This error occurs if you did not allow it at that time or if you manually denied the use of location information after that. Follow the instructions in this popup to allow the use of location information.

*Android 12 or later versions do not use location information.

14.2 Location information error B

ALLUX™ Remote Control

Turn on "Use Location"

OK

This error occurs when the location information function of the smartphone itself is not enabled. Enable the location information function of the smartphone.

*Android 12 or later versions do not use location information.

14.3 Bluetooth setting error

ALLUX™ Remote Control

No Bluetooth connection

OK

If Bluetooth is OFF, this App cannot communicate with ALLUX™. Turn ON Bluetooth with the function of the smartphone.

14.4 Connection to ALLUXTM error

ALLUX™ Remote Control

Password is incorrect.

OK

This error occurs when the wrong password was input on the "Connection to ALLUXTM" screen. Enter the password indicated on the charging port again.

14.5 Password error (3 times)

ALLUX™ Remote Control

Password was wrong 3 times. App closes when the "OK" button is pressed.

OK

This error occurs if you fail in entering the password 3 times. And then this App closes at once. When you start up this App again, you can enter the password again.

14.6 Wireless connection error

ALLUX™ Remote Control

Unable to connect Bluetooth

OK

This error occurs when wireless connection between ALLUXTM and Bluetooth on smartphone is failed. Try to turn ON the wireless connection of ALLUX™ referring to page 7

14.7 Wireless communication error

ALLUX™ Remote Control


Connection to ALLUX™ was failed

OK

This error occurs when communication between ALLUXTM and App on smartphone is failed. Enable wireless connection again referring to page 12.

If this occurs during a mode change, check the status of ALLUX™ and use it.

14.8 Safe posture error



If the user does not take a safe posture, ALLUXTM cannot change the settings. Assume a safe posture referring to page 6.

14) Error message popup

14.9 Hydraulic control error

ALLUX™ Remote Control

A warning requests you to refrain from use of ALLUX™. Contact the prosthetist.

OK

Because hydraulic control may be out of order, the control of ALLUXTM is stopped.

Contact the prosthetist to have maintenance service.

14.10 Device connection error in the vicinity

ALLUX™ Remote Control

Go to Settings-> Apps-> "ALLUX™ Remote Control"-> Permissions and turn on Nearby devices.

App closes when the "OK" button is pressed.

OK

The permission of "Nearby devices" is required to use "ALLUX $^{\text{TM}}$ Application Remote Control". Therefore, you need to have set to allow "Nearby devices" in the operation in page 10. This error occurs if you did not allow it at that time or if you manually denied after that. Follow the instructions in this popup to allow "Nearby devices"

14.11 Reconnect button error

ALLUX™ Remote Control

No prior device connection.

OK

This error is displayed when you tap the Reconnect button with no previously connected ALLUXTM. Make connection according to the regular procedure before using.

15 Troubleshooting

Problem	Check item	Remedy
The Application	Check that the operating system version is appropriate.	Update the operating system to Android 7 or later.
Remote Control	Check that the hard disk of the	Increase the free space on the hard disk.
cannot be installed.	smartphone etc. has a required	·
	free space.	
	Check that ALLUX [™] is recognized on the "Connection to ALLUX [™] "	Select ALLUX TM on the "Connection to ALLUX TM " screen.
	screen (page 13).	ALLINATM
	Check that ALLUX™	ALLUX™ cannot be connected with
	communication is not connected	multiple devices. If the Prosthetist is using
	with multiple devices.	the Adjustment App, ask the prosthetist to
	Ob1. 4b -4 Db44b :- "ON!"	disconnect the communication.
ALLUX™ cannot be	Check that Bluetooth is "ON" on	Turn ON Bluetooth on the smartphone.
connected.	the smartphone.	Perform the following three steps before
connected.	Cannot be connected even with	
	the above remedies.	reconnecting.
		(1)Reboot the ALLUX [™] power supply.
		(Insert the charger or the power OFF
		cap once and then remove it.)
		(2)Turn OFF the smartphone's Bluetooth
		once and then turn it back ON.
		(3)Restart the Application Remote Control.
Wireless connection	Check that the toe or heel setting	Check the setting with this App or the way
cannot be restored	is correct or the way of applying a	of applying a load again referring to page
even if a load is	load is correct.	7. If the wireless connection still cannot be
applied on the heel		restored, remove and insert the battery
or the toe 4 times		charger or the power OFF cap for
intermittently.		restoration.
	Check that the ALLUX™ wireless	Turn ON wireless connection referring to
	connection is ON.	page 7.
ALLUX™ is not	Check that battery for ALLUX™	Charge the battery for ALLUX TM .
indicated on the	has been charged.	
"Connection to	Check that multiple Apps are not	Close unnecessary Apps.
ALLUX TM " screen.	working at the same time.	
	Check that the Bluetooth function	Turn ON the Bluetooth function.
	is "ON" on the smartphone.	

15 Troubleshooting

	Check that the battery capacity for	Charge the battery for ALLUX [™] or smart
	ALLUX™ or smartphone is low	phone.
	battery status.	
Communication	Check ALLUX™ is used under the	Avoid using the device in an environment
between ALLUX™	specific wireless condition such as	where trains or vehicles frequently come
and App is easily	beside railway, highway, TV tower,	and go, or in an environment where there
disconnected.	airport, in exhibition and hospital.	are multiple wireless connections.
	Check if there are huge shields	Remove shields that block radio waves.
	against radio wave around	
	ALLUX™ user.	



Nablesco Corporation

Manufacturer

Nabtesco Corporation

Accessibility Innovations Company Assistive Products Department

35, Uozakihama-machi Higashinada-ku

Kobe, Japan 658-0024 TEL: +81-78-413-2724 FAX: +81-78-413-2725

https://mobilityassist.nabtesco.com/

Authorized representative for EU countries

PROTEOR SAS

6 rue de la Redoute 21850 Saint-Apollinaire France

TEL: +33 3 80 78 42 42 FAX: +33 3 80 78 42 15 cs@proteor.com

 ϵ

Contact

Please contact us if you find any page missing or disordered.

Nabtesco

Nablesco Corporation